

**Kelvion K°Bond** 

# COMPACTNESS & PERFORMANCE BONDED TOGETHER



#### **DESIGN & FUNCTION**

For decades, we have been supplying the oil & gas industry with reliable and efficient heat exchange technology for a wide range of applications. Our broad experience and knowledge of the market has enabled us to develop and enhance our product portfolio with innovations.

K°Bond, Kelvion's diffusion bonded heat exchanger, is ideal for applications involving extreme process temperatures and pressures. Combining design with welding expertise, K°Bond withstands pressures up to 1,000 bar and temperatures from cryogenic -200 to 600 °C, while providing significant savings in weight and footprint compared to common heat exchanger solutions.

K°Bond with its diffusion bonding technology is perhaps one of the most significant and game-changing solutions for projects with restricted space – May it be for offshore plants (e. g. as high pressure vaporizer) and reliquefaction on floating units.

#### **ADVANTAGES**

- ► PRESSURE RESISTANCE UP TO 1000 BAR
- ► WORKING TEMPERATURE RANGE FROM -200°C TO 600°C
- ► HIGH HEAT TRANSFER RATE THANKS TO FLUIDS PROXIMITY ALLOWING TEMPERATURE APPROACH UP TO 2°C
- ► LEAKAGE FREE AND SAFE
- **▶ HIGH RESISTANCE TO CYCLIC SERVICES**
- ► UP TO 6 TIMES SMALLER THAN
  CONVENTIONAL S&T HEAT EXCHANGER

### **K°BOND APPLICATIONS**



LNG



**GAS COMPRESSION OFFSHORE** 



**FSRU** 



**RENEWABLES** 





**HYDROGEN** 



**SUPERCRITICAL** CO,

## **K°BOND PERFORMANCE**








## **DIFFUSION BONDING**


- service and chemically etched on stainless steel plates.
- 1. Patterns are designed for each 2. Etched plates are stacked and welded through diffusion bonding process, converting them into one solid block of metal (core).
- 3. When required, multiple cores are welded together. Nozzles and headers are welded on cores to form final K°Bond.




Plate











**Diffusion bonding** 





Optimized in-house design software



Available in stainless steel 304L & 316L



Designed as per ASME rules, CE-marked and / or U-stamped